




**LIFT  
& SLIDE**

# HS-MAGIS40

DOUBLE GLAZING  $U_w=1,3 \text{ W/m}^2\text{K}$

TRIPLE GLAZING  $U_w=0,85 \text{ W/m}^2\text{K}$

Material	Wood-Aluminium	
Thermal insulation	 $U_w= 1,3 \text{ W/m}^2\text{K}$	 $U_w= 0,85 \text{ W/m}^2\text{K}$
Insulating glass	 Double glazing thickness 32mm	 Triple glazing thickness 52mm
Acoustic insulation	 Not declared	
Security hardware	 Up to RC2	

Air permeability	 CLASS 4
Water tightness	 CLASS 9A
Wind load resistance	 CLASS C4/B5

The thermal transmittance values are calculated according to UNI EN 10077/1-2018, UNI EN 10077/2-2018, UNI EN 10456-2008, UNI EN 673-2011 standards, in reference to a lift-sliding door Plan A - WxH (2800x2400mm,  $\psi_g= 0,04 \text{ W/mK}$ )

The air-water-wind tightness performances are certified in reference to a lift-sliding door Plan A - WxH (2800x2400mm)



## HS-MAGIS40 - 32mm glass SOFT WOOD

$U_g \text{ W/m}^2\text{K}$	$U_w \text{ W/m}^2\text{K}$
1,0	-» 1,3
1,1	-» 1,4
1,2	-» 1,5
1,3	-» 1,6
1,4	-» 1,7
1,5	-» 1,8
1,6	-» 1,8

## HS-MAGIS40 - 52mm glass SOFT WOOD

$U_g \text{ W/m}^2\text{K}$	$U_w \text{ W/m}^2\text{K}$
0,5	-» 0,85
0,6	-» 0,95
0,7	-» 1,0
0,8	-» 1,1
0,9	-» 1,2
1,0	-» 1,3
1,1	-» 1,4